



Driving 16ga Fasteners from 1 1/4" to 2 1/2" the FinishPro32 provides all the versatility a professional contractor will ever need, combined with features such as a thumbwheel adjustable depth of drive and a reversed safety foot, the FinishPro32 will be the only 16ga nailer needed

Applications:

Baseboards, cabinets, case goods, chair rail, crown molding, decorative trim, door & window casing-sash & millwork, bookshelves, exterior trim interior trim,

FinishPro® 32 Features and Benefits:

- Thumb wheel adjustable depth-of-drive
- 360° adjustable exhaust – keeps oil and dust away from the work surface
- Belt hook – for convenience
- Stretch comfort grip – for comfort and control
- EZ-Clear® removes jams fast and easy
- No-mar pad – to protect work materials
- Rear bumper – to protect the work surface
- Available in dual action or restrictive fire
- One-year warranty
- Includes case, fitting, oil, wrench and manual

Specifications:

Item#: 1X0201N Sequential Actuation w/case

Tool Weight: 4.3 lbs (1.8 kg)

Height: 113/8" (349 mm)

Length: 12" (304 mm)

Nail Capacity: 110

Reg. Operating Pressure: 70-120 psig


Mode of Operation: Tool is available with either contact actuation or sequential trigger mechanism.

Fastener Specifications:

Gauge: 16

Fastener Range: 1-1/4" – 2-1/2"

Finish: Galvanized





Always read the Operators Manual and Safety Instructions with all tools to ensure proper use and safety precautions or contact Senco for more information on our trigger systems. Choose the right trigger system for your specific needs! For additional information on how Senco Fastening Solutions will save you time, reduce costs, and increase quality, call our toll-free Action Line: 1-800-543-4596 to find your nearest Authorized Senco Dealer or Distributor. Visit our web site at: www.senco.com

Sequential Actuation Trigger (also known as restrictive trigger or trigger fire) operates in the following a sequence - depress the safety element at the nose of tool against the work surface then pull the trigger. After each fastener is driven, release the trigger and lift the tool off the work surface before starting the sequence again. This trigger is recommended and acceptable for most applications.

Contact Actuation Trigger (also known as dual action, bounce or bottom fire) operates in the following sequence- pull the trigger first and keep the trigger pulled while moving the tool along the work surface with a bouncing motion, depressing the safety element at the nose of the tool against the work surface where the fastener is to be driven. This trigger is recommended for use by trained professionals only in high production or volume applications.